



Sanderson

ACTIVE EMULSION

DESCRIPTION

Active Emulsion offers ultimate durability. For use on interior walls, metal and woodwork, it's tougher than traditional Emulsions, making it easier to clean and the ideal solution for high traffic areas. A fast drying, low odour, low sheen finish ideal for use where durability and performance is important.

KEY PROPERTIES

- Ultimate durability and performance.
- Washable and stain resistant
- Ideal for high wear/traffic areas such as hallways, kitchens and children's bedrooms.
- Low sheen finish

PREPARATION

All surfaces should be sound, clean, dry and free from grease. Remove any loose or flaking paint. Rub down sound glossy surfaces with fine waterproof abrasive paper and rinse thoroughly before applying a pre-coat of a Water/Acrylic Primer Undercoat. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. Seal absorbent surfaces with a solution of up to 1 part water to 4 parts Active Emulsion. Prime bare timber and metal surfaces with an appropriate primer. Allow radiators to cool before painting.

APPLICATION

Stir well before use and apply by brush, roller or paint pad. When using a roller, use a medium pile synthetic type. Do not overfill the tray. Ensure roller is loaded evenly. If using a brush, load generously. Apply liberally and evenly; avoid overspreading.

CLEANING

Remove as much product as possible from equipment before cleaning. Clean immediately after use in warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty wastes paint into drains or watercourses.

PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one and octhilineone (ISO). May produce an allergic reaction.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children

- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. Safety data sheet available on request.

RECOMMENDED USES

Suitable for interior use

TYPE OF SUBSTRATE

Interior walls and ceilings. Suitably primed woodwork, metal and radiators.

COLOUR RANGE

154 colours.

FINISH

Low sheen

VOLUME SOLID

35%

COVERAGE

Approximately 12 square metres per litre depending on the nature and porosity of the surface.

DRYING TIME

Touch dry in 1 - 2 hours. Recoatable after 2 - 4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

CLEANER

Clean water

VOC CONTENT

- Low VOC Content 0.3 - 7.99%
- VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.
- EU limit value for this product (Cat A/a): 30g/l (2010).
- This product contains max 15g/l VOC.

FILM THICKNESS

Wet: 83µm, Dry: 29µm.

SIZES

2.5 Litre, 5 Litre



Sanderson

WATER BASED EGGSHELL

DESCRIPTION

Water Based Eggshell is a premium quality, water-based, low sheen finish formulated for interior use on walls, ceilings, wood and metal surfaces. It provides a low odour, quick drying finish that is resistant to condensation and yellowing, making it ideal for use in kitchens, bathrooms, hallways and conservatories.

KEY PROPERTIES

- A quick drying, low odour, low sheen finish for interior use.
- Produces a smooth, washable surface that resists condensation.
- Tough, durable and non-yellowing.
- High opacity and hardwearing.

PREPARATION

All surfaces should be sound, clean, dry and free from grease. Remove any loose or flaking paint. Prime bare surfaces with the appropriate Primer. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly before applying a pre-coat of Water/Acrylic Based Primer Undercoat. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

APPLICATION

Stir well. Easy to apply by brush or roller. Seal absorbent surfaces with a coat of Acrylic Eggshell thinned up to 10% with clean water. If more than one can of a colour is to be used in the same area, intermix before use. Do not apply in temperatures below 10°C.

CLEANING

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into rains or watercourses.

PRECAUTIONS

- Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one (EC no.247-500-7) and 2-methyl-2H-isothiazol-3-one (EC no.220-239-6) (3:1), octhiline (ISO) and 1,2-benzisothiazol-3(2H)-one,. May produce allergic reaction.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.

- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

RECOMMENDED USES

Suitable for interior/Exterior use.

TYPE OF SUBSTRATE

Wood, metal and plaster. Also suitable for use on wallboards, concrete, cement rendering, brickwork and blockwork in internal situations.

COLOUR RANGE

154 colours.

FINISH

Low sheen

VOLUME SOLID

36%

COVERAGE

Approximately 10 - 12 square metres per litre depending on the nature and porosity of the surface

DRYING TIME

Touch dry in 1 - 2 hours. Recoatable after 2 - 4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

CLEANER

Clean water

VOC CONTENT

- Low VOC Content 0.3-7.99%
- VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.
- EU limit value for this product (Cat A/a): 30g/l (2010).
- This product contains max 10g/l VOC.

FILM THICKNESS

Wet: 83µm, Dry: 30µm.

SIZES

1 Litre, 2.5 Litre



Sanderson

OIL - BASED EGGSHELL

DESCRIPTION

Eggshell is a premium quality, traditional alkyd based mid sheen finish formulated for interior and exterior. Use on wood and metal surfaces. It provides a smooth, even surface that is washable and resistant to condensation.

KEY PROPERTIES

- A traditional solvent-based mid sheen finish for interior and exterior. Use on wood and metal.
- Ideal for kitchens, Bathrooms and conservatories
- Resistant to steam and condensation.
- Produces a smooth, washable, hard wearing finish.

PREPARATION

All surfaces should be sound, clean, dry and free from grease. Remove any loose or flaking paint. Prime bare surfaces with the appropriate Wood or Metal primer. Rub down previously painted surfaces fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

APPLICATION

Stir well. Easy to apply by brush or roller. Do not apply over polystyrene surfaces.

CLEANING

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- **FLAMMABLE**
- Contains 2-butanone oxime. May produce an allergic reaction.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- **IF ON SKIN:** Wash with plenty of water. Do not use

solvent thinners or White Spirit.

- **IF SWALLOWED:** Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- Not recommended for interior use on large surface areas, or in confined spaces.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.
- Safety data sheet available on request.

RECOMMENDED USES

Suitable for interior and exterior use.

TYPE OF SUBSTRATE

- Wood and metal.
- Do not use over large surface areas internally.

COLOUR RANGE

154 colours.

FINISH

Mid sheen

VOLUME SOLID

61%

COVERAGE

Approximately 17 square metres per litre, depending on the nature and porosity of the surface.

DRYING TIME

Recoat after 16 - 24 hours under normal drying conditions. Touch dry 3 - 4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

CLEANER

White spirit

VOC CONTENT

- High VOC content 25 - 50%
- VOC's (Volatile Organic Compounds) contribute to atmospheric pollution. EU limit value for this product (Cat A/d): 300g/l (2010). This product contains max 300g/l VOC

FILM THICKNESS

Wet: 50µm, Dry: 31µm.

SIZES

1 Litre, 2.5 Litre